



SPECIFICATIONS

Product Description: **DUCTING,**
 Part Number: **9500-06, 9500-15, 9500-25**
 Style: **8" (20.3 cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- PVC Coated
- Temperature Range: -20°F to 180°F (-28.8°C to 82.22°C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Yellow color with black weather-strip
- Fastening cuffs at both ends



AVAILABLE:

Part No.	Diameter In (cm)	Length In (m)	End-Straps
9500-06	8" (20.3 cm)	6' (1.82 m)	Dual
9500-15	8" (20.3 cm)	15' (4.57 m)	Dual
9500-25	8" (20.3 cm)	25' (7.62 m)	Dual

ACCESSORIES:

Part No.	Ducting Size In (cm)	Description
9500-01	8" (20.3)	Duct to Duct Connector, with raised lip
9510-50	8" (20.3)	Manhole Ventilation Passthru, MVP
9500-35	8" (20.3)	Storage Rack for 8" (20.3 cm) Ducting, up to 25' (7.62 m) Ducting
9500-45	8" (20.3)	Storage Bag