



SPECIFICATIONS

Product Description: **8" (20.3 cm) AIR BAG BLOWER SYSTEM**
Part Number: **9535-08, 9535-08L**
Style: **AXIAL FAN**

GENERAL DESCRIPTION:

8" (20.3 cm) blower system with ducting is built into a heavy-duty bag. Zippered ends allow blower use without removing from bag. Combination Axial 8" (20.3 cm) blower, 15' (4.57 m) or 25' (7.62 m) duct and custom storage bag to house the system. Certified to CSA Standard C22.2 No 113.



CONSTRUCTION:

- Lightweight, metal 8" (20.3 cm) blower
- Super quiet
- Carry handle with molded-in 2-speed switch
- Steel/powder coated housing and grills
- Unique bag with openings for plug/cord, inlet and outlet
- Durable reinforced polyester bag
- Easy to carry and store
- All-in-one unit for ease of operation
- Duct mounted on the blower and stored inside bag
- Both carrying handle and shoulder strap allows for easy transportation

MOTOR:

HP: 1/4 HP
Certifications: UL Recognized, CSA Certified
Voltage/Hz: 115V AC, 60 Hz, Single Phase
Max RPM: 3300 (loaded at 120 Volts, 60 Hz)
Amps: 1.4A
Cord: 6' (1.82 m) AWG
Switch: 2-speed on/off switch
Plug: NEMA 5-15P 125V

FAN:

- Polypropylene seven blade fan

DUCTING:

- Single-ply lightweight vinyl/polyester, PVC coated 180° F (82.2° C) temperature resistant
- Non-collapsible retractable design
- Yellow with black wear-strip and integrated nylon attachment strap on one end

DIMENSIONS:

Length	Width	Height	Weight
27" (68.5 cm)	15" (38.1 cm)	12" (30.4 cm)	25 lbs. (11.3 kg)

FLOW RATES: (free air calculated at blower)
760 CFM (1291.2 m³/hr)

AVAILABLE:

9535-08DC 8" (20.3 cm) DC blower system with 15' (4.57 m) ducting
9535-08LDC 8" (20.3 cm) DC blower system with 25' (7.62 m) ducting