



SPECIFICATIONS

Product Description: **8" (20.3 cm) AXIAL AC PLASTIC MINI-PAK BLOWER**
 Part Number: **9532-15, 9532-25, 9532-15E*, 9532-25E***
 Style: **ALL-IN-ONE BLOWER WITH DUCTING**

GENERAL DESCRIPTION:

This high output blower's compact design stores ducting inside the blower housing for an all-in-one unit for ease of operation, transportation, and storage! Available with either 15' (4.75 m) or 25' (7.62 m) of ducting, this new design is now the lightest and shortest in the industry!

CONSTRUCTION:

- Polyethylene housing
- Lightweight, corrosion-, UV- and chemical-resistant
- Super quiet, in "safety orange"
- Carry handle molded into blower and canister housing
- Steel powder coated grill
- A separate 12" (30.48 cm) duct (not included) can be attached to the intake side of the blower to draw air



MOTOR:

HP: 1/3 HP
 Voltage/Hz: 115V-230V AC, 50/60 Hz, Single Phase, All World Motor
 RPM: 2850/3350
 Amps: 1.5A-0.7A (50 Hz) / 1.9A-1.0A (60 Hz)
 Cord: 6' (1.83 m)
 Plug: NEMA 5-15P

FAN:

- 9-blade Polypropylene fan

DUCTING:

- Retractable, non-collapsible design
- Single-ply, PVC coated vinyl and polyester materials, temperature resistant up to 180° F (82.2° C)
- Yellow color with black wearstrip and integrated nylon attachment strap
- Class 1 hard drawn spring steel wire helix that meets ASTM 227 specs

BLOWER DIMENSIONS:

P/N	Length	Width	Height	Weight
9532-15, 9532-15E*	17 ½" (44.5 cm)	11 ¼" (28.6 cm)	13 ½" (34.3 cm)	19.4 lbs. (8.8 kg)
9532-25, 9532-25E*	17 ½" (44.5 cm)	11 ¼" (28.6 cm)	13 ½" (34.3 cm)	23.2 lbs. (10.5 kg)

FLOW RATES:

P/N	Straight	One 90° Bend	Two 90° Bends
9532-15, 9532-15E*	791 CFM (1343 m ³ /hr)	703 CFM (1194 m ³ /hr)	621 CFM (1055 m ³ /hr)
9532-25, 9532-25E*	760 CFM (1291 m ³ /hr)	674 CFM (1145 m ³ /hr)	602 CFM (1022 m ³ /hr)

*E version blowers are 220V, 50 Hz