

## Fitting Savers Operating Instructions

1. Cut problem or damaged pipe off as close to the fitting as possible.
2. Select the fitting saver or fitting reamer.
3. Install the fitting saver or reamer into a standard 3/8" drill.
4. Insert saver or reamer into the pipe. Start to remove the pipe. Drill and lightly push the fitting saver into the fitting. Hold the saver as straight as possible to prevent over sizing the fitting. Continue cutting in one smooth operation until pipe is completely removed.

**Wheeler Rex ■ Ashtabula Ohio**  
**Tel: 800-321-7950 or 440-998-2788**  
**wheeler@wheelerrex.com ■ www.wheelerrex.com**

## Fitting Savers Operating Instructions

1. Cut problem or damaged pipe off as close to the fitting as possible.
2. Select the fitting saver or fitting reamer.
3. Install the fitting saver or reamer into a standard 3/8" drill.
4. Insert saver or reamer into the pipe. Start to remove the pipe. Drill and lightly push the fitting saver into the fitting. Hold the saver as straight as possible to prevent over sizing the fitting. Continue cutting in one smooth operation until pipe is completely removed.

**Wheeler Rex ■ Ashtabula Ohio**  
**Tel: 800-321-7950 or 440-998-2788**  
**wheeler@wheelerrex.com ■ www.wheelerrex.com**

## Fitting Savers Operating Instructions

1. Cut problem or damaged pipe off as close to the fitting as possible.
2. Select the fitting saver or fitting reamer.
3. Install the fitting saver or reamer into a standard 3/8" drill.
4. Insert saver or reamer into the pipe. Start to remove the pipe. Drill and lightly push the fitting saver into the fitting. Hold the saver as straight as possible to prevent over sizing the fitting. Continue cutting in one smooth operation until pipe is completely removed.

**Wheeler Rex ■ Ashtabula Ohio**  
**Tel: 800-321-7950 or 440-998-2788**  
**wheeler@wheelerrex.com ■ www.wheelerrex.com**

## Fitting Savers Operating Instructions

1. Cut problem or damaged pipe off as close to the fitting as possible.
2. Select the fitting saver or fitting reamer.
3. Install the fitting saver or reamer into a standard 3/8" drill.
4. Insert saver or reamer into the pipe. Start to remove the pipe. Drill and lightly push the fitting saver into the fitting. Hold the saver as straight as possible to prevent over sizing the fitting. Continue cutting in one smooth operation until pipe is completely removed.

**Wheeler Rex ■ Ashtabula Ohio**  
**Tel: 800-321-7950 or 440-998-2788**  
**wheeler@wheelerrex.com ■ www.wheelerrex.com**

## Fitting Savers Operating Instructions

1. Cut problem or damaged pipe off as close to the fitting as possible.
2. Select the fitting saver or fitting reamer.
3. Install the fitting saver or reamer into a standard 3/8" drill.
4. Insert saver or reamer into the pipe. Start to remove the pipe. Drill and lightly push the fitting saver into the fitting. Hold the saver as straight as possible to prevent over sizing the fitting. Continue cutting in one smooth operation until pipe is completely removed.

**Wheeler Rex ■ Ashtabula Ohio**  
**Tel: 800-321-7950 or 440-998-2788**  
**wheeler@wheelerrex.com ■ www.wheelerrex.com**

## Fitting Savers Operating Instructions

1. Cut problem or damaged pipe off as close to the fitting as possible.
2. Select the fitting saver or fitting reamer.
3. Install the fitting saver or reamer into a standard 3/8" drill.
4. Insert saver or reamer into the pipe. Start to remove the pipe. Drill and lightly push the fitting saver into the fitting. Hold the saver as straight as possible to prevent over sizing the fitting. Continue cutting in one smooth operation until pipe is completely removed.

**Wheeler Rex ■ Ashtabula Ohio**  
**Tel: 800-321-7950 or 440-998-2788**  
**wheeler@wheelerrex.com ■ www.wheelerrex.com**