

2315

The hazard horizon is bright. With Class I, II, III – Division 1 and IECEx ia Safety Certification, 115 lumens and 75 meters of spot beam distance, the Pelican™ 2315 flashlight stretches light across dark, hazardous environments without being a source of ignition. Engineered with an aluminum core and ABS overmolded plastic, these flashlights are built for rough handling and can survive hard drops. Plus, the

flashlights are built for rough handling and can survive hard drops. Plus sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves. Pelican[™] 2315 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Built Pelican tough
- 2 AA Batteries (included)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- Class I, II, III Division 1 / IECEx ia Safety Certified
- IPX8 1m waterproof
- Helmet mount (included)



DIMENSIONS

Length

6.22" (15.8 cm)

MATERIALS

Body	ABS
Body D-Ring	NBR
Lens	PC
Shroud	ABS
Clip	ABS

COLORS

High Visibility Yellow

LIGHT SPECS

Lamp Type	LED		
POWER			

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	2
Batteries Included	yes
Volts	3.0v

WEIGHT

Weight With Batteries4.6 oz (130 gr)Weight Without
Batteries2.8 oz (79 gr)

SWITCH

Switch Type Light Modes Momentary Push Button High

CERTIFICATIONS

Class I, Division 1 Class II, Division 1 Class III, Division 1 IECEx ia

FL1 STANDARD	HIGH
3MZ	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 07-11-22