



LSR - SERIES
LOW LEVEL - DEWATERING PUMP

SPECIFICATIONS

FEATURES

1. Semi-vortex, urethane rubber impeller with ethylene propylene rubber casing increases wear resistance when pumpage contains abrasive particles.
2. Double inside mechanical seals with silicon carbide faces, (both top and bottom) running in an oil filled chamber and further protected by a lip seal running against a replaceable 430 stainless steel shaft sleeve provides for the most durable seal design available.
3. Highly efficient, continuous duty, air filled, copper wound motor with class E insulation minimizes the cost of operation.
4. Built in thermal & amperage sensing protector prevents motor failure due to

overloading or accidental run -dry conditions.

5. Double shielded, permanently lubricated, high temperature C3 ball bearings rated for a B-10 life of 60,000 hours extend operational life.
6. Top discharge, flow-thru design enables operation at low water levels (3/16") for extended periods.

APPLICATIONS

1. Residential, commercial, industrial wastewater and construction site drainage.
2. Effluent transfer.
3. Decorative waterfalls and fountains.
4. Raw water supply from rivers or lakes.



SPECIFICATIONS

- Discharge Size
- Horsepower Range
- Performance Range Capacity Head
- Maximum water temperature
- Materials of Construction
 - Casing
 - Impeller
 - Shaft
 - Motor Frame
 - Fasteners
- Mechanical Seal
 - Elastomers
- Impeller Type
- Solids Handling Capability
- Bearings
- Motor Nomenclature
 - Type, Speed, Hz.
 - Voltage, Phase
 - Insulation
- Accessories
- Operational Mode

STANDARD

- 2" NPT (50 mm)
- 2/3 HP. (.48 Kw)
- 15.9 ~ 62.4 GPM. (0.06 ~ 0.24 m³/min)
- 13.1 ~ 39.5 Ft. (4.00 ~ 12.04 m)
- 104° F. (40° C.)
- Ethylene Propylene Rubber
- Urethane Rubber
- 403 Stainless Steel
- Aluminum alloy
- 304 Stainless Steel
- Silicon Carbide
- NBR (Nitril Butadiene Rubber)
- Semi-vortex, solids handling
- 0.0236" (6mm)
- Prelubricated, Double Shielded
- Air Filled, 3600 RPM, 60 Hz.
- 115 / 230V., 1 Phase
- Class E
- Submersible Power Cable 32' (10.0 m)
- Manual

Length as Required,
TS-301 Float Switch