



Model 950XL

Double Check Valve Assembly

Application

Designed for installation on water lines to protect against both backsiphonage and backpressure of polluted water into the potable water supply. Assembly shall provide protection where a potential health hazard does not exist.

Standards Compliance

(All sizes approved horizontal. Vertical approvals as listed below.)

- ASSE® Listed 1015 (vertical 3/4", 1 1/2" & 2")
- IAPMO® Listed (vertical 1 1/2", 2")
- CSA® Listed (vertical 3/4", 1 1/2" & 2")
- AWWA Compliant C510 (vertical 3/4")
- Approved by the Foundation for Cross Connection Control and Hydraulic Research at the University of Southern California (vertical 3/4")
- City of Los Angeles Approved (vertical 1 1/2", 2")
- NYC MEA 426-89-M VOL 3

Materials

Main valve body	Cast Bronze ASTM B 584
Access covers	Cast Bronze ASTM B 584
Internals	Stainless Steel, 300 Series
Elastomers	Silicone (FDA approved) Buna Nitrile (FDA approved)
Polymers	Noryl™
Springs	Stainless steel, 300 series

Features

Sizes: 3/4", 1", 1 1/2", 2"

Maximum working water pressure	175 PSI
Maximum working water temperature	180°F
Hydrostatic test pressure	350 PSI
End connections Threaded	ANSI B1.20.1




Options

(Suffixes can be combined)

- ☐ - with full port QT ball valves (standard)

Accessories


- ☐ Repair kit (rubber only)
☐ Thermal expansion tank (Model XT)
☐ QT-SET Quick Test Fitting Set



Dimensions & Weights (do not include pkg.)



MODEL SIZE		DIMENSIONS (approximate)												WITH BALL VALVES	
		A		B LESS BALL VALVES		C		D		E		F			
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg
3/4	20	11 1/4	286	7	178	1 1/2	38	3	76	3 1/2	89	3	76	7	3.2
1	25	12 1/4	311	7	178	1 1/2	38	3	76	3 1/2	89	3	76	12	5.4
1 1/2	40	17 1/8	435	10 9/16	268	2	51	3 1/2	89	4 1/2	114	4 1/2	114	22	10
2	50	18 1/4	460	10 9/16	268	2	51	3 1/2	89	4 1/2	114	4 1/2	114	28	12.7

*Size 1-1/4" Discontinued

MODEL 950XL 3/4", 1", 1 1/2" & 2" (STANDARD & METRIC)**Typical Installation**

Local codes shall govern installation requirements. To be installed in accordance with the manufacturer's instructions and the latest edition of the Uniform Plumbing Code. Unless otherwise specified, the assembly shall be mounted at a minimum of 12" (305mm) and a maximum of 30" (762mm) above adequate drains with sufficient side clearance for testing and maintenance. The installation shall be made so that no part of the unit can be submerged.

Capacity thru Schedule 40 Pipe				
Pipe size	5 ft/sec	7.5 ft/sec	10 ft/sec	15 ft/sec
1/8"	1	1	2	3
1/4"	2	2	3	5
3/8"	3	4	6	9
1/2"	5	7	9	14
3/4"	8	12	17	25
1"	13	20	27	40
1 1/4"	23	35	47	70
1 1/2"	32	48	63	95
2"	52	78	105	167

**OUTDOOR INSTALLATION****INDOOR INSTALLATION****Specifications**

The Double Check Valve Backflow Preventer shall be ASSE® Listed 1015, and supplied with full port ball valves. The main body and access covers shall be bronze (ASTM B 584), the seat rings and all internal polymers shall be Noryl™ and the seat disc elastomers shall be silicone. The first and second checks shall be accessible for maintenance without removing the device from the line. The Double Check Valve Backflow Preventer shall be a ZURN WILKINS Model 950XL.