

Graphite Lubricant

Safety Data Sheet

SECTION 1: Product and company identification

Product name : Graphite Lubricant
Use of the substance/mixture : Dry lubricant
Product code : 0336
Company : CORE & MAIN LP
1830 CRAIG PARK COURT
ST. LOUIS, MO 63146 - US
T 314-432-4700
Emergency number : 314-432-4700

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification
Flam. Liq. 3 H226
Asp. Tox. 1 H304

2.2. Label elements

GHS US labelling
Hazard pictograms (GHS US) :



GHS02 GHS08

Signal word (GHS US) : Danger
Hazard statements (GHS US) : Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof lighting, electrical equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear eye protection, protective clothing, protective gloves.
If swallowed: Immediately call a doctor, a POISON CENTER.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Do NOT induce vomiting.
In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to comply with local/regional/national/international regulations..

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Hydrotreated Light Alkanes (Solvent)	(CAS-No.) 64742-47-8	65 – 85	Not classified
Alkanes, C14-16 (Solvent)	(CAS-No.) 90622-46-1	7-13	Asp. Tox. 1, H304
Hydrotreated Heavy Alkanes (Solvent)	(CAS-No.) 64742-52-5	5-10	Carc. 1B, H350

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Graphite Lubricant

Safety Data Sheet

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : If you feel unwell, seek medical advice. May cause cancer. May be fatal if swallowed and enters airways.
- Symptoms/effects after inhalation : May cause respiratory irritation. Dizziness. Nausea. Feeling of weakness. Headache. Unconsciousness.
- Symptoms/effects after skin contact : Contact during a long period may cause light irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Risk of aspiration pneumonia. Gastrointestinal complaints. Nausea. Cramps. Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical powder. Carbon dioxide. Alcohol-resistant foam.

5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Vapours may travel long distances along ground before igniting/flashing back to vapour source.
- Reactivity : Thermal decomposition may produce oxides of carbon and sulfur. Toxic fumes may be released.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Protective goggles. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. No naked flames or sparks.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, collect/pump into suitable containers.
- Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation. Take up liquid spill into inert absorbent material, e.g.: sand/earth. Clean contaminated surfaces with a soap solution.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Graphite Lubricant

Safety Data Sheet

Precautions for safe handling	: Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Do not breathe vapours. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Handle and open the container with care. Keep away from sources of ignition - No smoking. Take precautions against electrostatic charges. Obtain special instructions before use. Remove contaminated clothing immediately.
Hygiene measures	: Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from: sparks, open flames, excessive heat.
Incompatible products	: Oxidizing agent.
Incompatible materials	: Sources of ignition.
Storage area	: Store away from heat. Store in a cool area. Store in a dry area. Store in a well-ventilated place. Keep locked up.
Special rules on packaging	: Keep only in original container. meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Alkanes, C14-16 (90622-46-1)

Not applicable

Hydrotreated Heavy Alkanes (64742-52-5)

Not applicable

Hydrotreated Light Alkanes (64742-47-8)

Not applicable

8.2. Exposure controls

Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Protective clothing. Protective goggles. Safety glasses.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Black, Liquid
Odour	: solvent odor
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 130 °F Closed Cup
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20°C	: No data available
Density	: 0.85 g/ml
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available

Graphite Lubricant

Safety Data Sheet

VOC content : 40 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition may produce oxides of carbon and sulfur. Toxic fumes may be released.

10.2. Chemical stability

Flammable liquid and vapour. Heating may cause a fire or explosion.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Alkanes, C14-16 (90622-46-1)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.8 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified.

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation : May cause respiratory irritation. Dizziness. Nausea. Feeling of weakness. Headache. Unconsciousness.

Symptoms/effects after skin contact : Contact during a long period may cause light irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Risk of aspiration pneumonia. Gastrointestinal complaints. Nausea. Cramps. Vomiting.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to comply with local/regional/national regulations.

Graphite Lubricant

Safety Data Sheet

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description (DOT) : UN1993 Flammable liquids, n.o.s. (Aliphatic Hydrocarbons), 3, III
UN-No.(DOT) : UN1993
Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : B1,B52,IB3,T4,TP1,TP29
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
DOT Vessel Stowage Location : A

Additional information

Other information : When transported by ground in non-bulk containers, this product utilizes the exception found under 49 CFR 173.150. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

Graphite Lubricant

Safety Data Sheet

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.