

Lubricant

Product # 300

Lubricates, penetrates & demoisurizes

This premium lubricating oil penetrates threads, cracks and joints to lubricate metal surfaces and loosen rusted parts. It not only displaces moisture, but it also seals the surface to protect against future rust and corrosion. Its light blend of oils and inhibitors is an ideal tool for mechanics, machinists, toolmakers, pipe fitters, plumbers and other maintenance professionals.

Use On:

- Pipes and plumbing
- Machinery
- Tools and Equipment

Effective Against:

- Prevents rust and corrosion
- Penetrates frozen threads

Features and Benefits

- Protects against corrosion to extend the working life of machinery.
- Displaces and seals out moisture.
- Saves on production, maintenance and repair time.

Properties

| | |
|-----------------------|--------------------|
| Appearance..... | Brown liquid |
| Fragrance..... | Petroleum |
| Specific gravity..... | 0.82 |
| Flash point..... | 165°F |
| Stability..... | 1 year |
| Solubility..... | Insoluble in water |

Directions Complete directions on product label

Apply generously to all surfaces needing protection by brush, spray, swab or by dipping. Reapply as needed.

Active Ingredients

| | |
|---|------------|
| Hydrotreated Light Alkanes..... | 64742-47-8 |
| Alkanes C14-16..... | 90622-46-1 |
| Hydrotreated Middle Alkanes..... | 64742-46-7 |
| Hydrocarbon Waxes, Petroleum, Oxidized..... | 64743-00-6 |
| Barium Sulphonate..... | 61790-48-5 |

CAS Number


Safety

Danger – May be fatal if swallowed and enters airways.. Keep out of reach of children

DOT Shipping (ground transportation)

| | |
|-----------------------|------|
| Proper Shipping Name: | None |
| Class: | None |
| ID Number: | None |
| Packing Group: | None |

NFPA RATINGS



Quantities

- 55 gallon
- 35, 30 & 20 gallon
- 5 or 6 gallon
- 6 X 1 gallon
- 4 X 1 gallon

