

Technical Information

Canadian Part Numbers are shown in parentheses. V/B = Vehicle Bracket Included.

Model	2.5 ABC V/B	5 ABC V/B	10 TALL ABC	10S ABC	20S ABC	30S ABC	
Pt. # Alum. Valve	13315 (13390)	10914 (10990) 25614 (25690)	11340 (11390)	11310 (11320)	12120 (12195)	N/A	
Pt. # Brass Valve	N/A	10915 (10995) 25615 (25695)	11341 (11349)	N/A	12121 (12196)	12905 (12915)	
Agent Capacity	2.5 lb. (1.13 kg)	5 lb. (2.27 kg)	5 lb. (2.27 kg)	10 lb. (4.54 kg)	10 lb. (4.54 kg)	20 lb. (9.07 kg)	30 lb. (13.6 kg)
UL/ULC Rating	1-A:10-B:C	3-A:40-B:C	3-A:40-B:C	4-A:80-B:C	4-A:60-B:C	10-A:120-B:C	10-A:160-B:C
Temperature Range	-65° to 120°F (-54° to 49°C)						
Discharge Time	9 sec	14 sec	14 sec	22 sec	18 sec	27 sec	32 sec
Discharge Range ft (m)	9-15 (2.7-4.6)	12-18 (3.7-5.5)	12-18 (3.7-5.5)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	15-21 (4.6-6.4)	25-30 (7.6-9.1)
Operating Pressure	100 psi (689 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)	195 psi (1344 kPa)
Mounting Type	Vehicle	Wall	Vehicle	Wall	Wall	Wall	Wall
USCG Approval	Type B:C Size I	Type A Size II	Type A Size II	Type A Size II	Type A Size II	Type A Size II	Type A Size II
		Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II	Type B:C Size III	Type B:C Size IV
Ship Weight	5.5 lb. (2.5 kg)	10 lb. (4.5 kg)	10.25 lb. (4.7 kg)	18.25 lb. (8.3 kg)	18.75 lb. (8.6 kg)	33.5 lb. (15.2 kg)	52.25 lb. (23.7 kg)
Unit Height	14.75 in (37.5 cm)	16.375 in (41.6 cm)	16.375 in (41.6 cm)	21 in (53.3 cm)	16.75 in (42.5 cm)	21.25 in (53.8 cm)	27.375 in (69.4 cm)
Unit Width	4.875 in (12.4 cm)	7.25 in (18.4 cm)	7.25 in (18.4 cm)	7.75 in (19.7 cm)	8.25 in (21 cm)	8.75 in (22.2 cm)	8.75 in (22.2 cm)
Unit Diameter	3.375 in (8.6 cm)	4.25 in (10.8 cm)	4.25 in (10.8 cm)	5.125 in (13 cm)	6 in (15.2 cm)	7.5 in (19.1 cm)	7.5 in (19.1 cm)