
## NEW AND IMPROVED MAINGUARD HYDRANTS!

New Design and Standard Features Combine to Deliver the **BEST VALUE** for You!





813 HEMPSTEAD STREET / ST. LOUIS, MISSOURI 63102 314-231-8738 FAX# 314-231-2820 http://www.hydrants.com Call Toll Free 1-888-HYDRANT

## The MainGuard hydrant is built better than any other hydrant in its class.


The features available on this model include:

- 2<sup>1</sup>/<sub>2</sub>" **NST Nozzle.** Also available in any smaller size.
- Traffic Break-away. The MainGuard is designed to break easily at ground level.
- Security. A locking cover prevents water theft and protects MainGuard from the elements.
- **Easy Repair.** You'll never need a shovel to repair the MainGuard. Remove two bolts and you can take the inner workings out for easy repair and replacement.
- Brass Working Parts. All the moving parts are enclosed and made from high quality brass for greater durability and wear.
- **■** Full Draining Capabilities. The MainGuard drains to prevent freezing after flushing.
- 2" FIP Inlet. Inlet can come in from the side, or from the bottom. (As shown).
- Underground Model Available. The #78 MainGuard blow-off hydrant can be placed in a meter box if an underground installation is desired.

MainGuard hydrants are recommended for water main flushing purposes only. Please see our Eclipse line of hydrants for all other applications.

1-800-231-3990







314-231-8738 FAX# 314-231-2820 http://www.hydrants.com

Flushing and Sampling Systems


At the end of the main - it's MainGuard

## MAINGUARD NO. 77 BLOW-OFF HYDRANT (SPECIFY OUTLET) GROUND LINE ~ VALVE BOX \* -SPECIFY DEPTH OF BURY 2" SUPPLY PIPE\* CONNECTION TO MAIN\* 2" FIP HORIZONTAL INLET CURB STOP VALVE\* CRUSHED ROCK \* = BY OTHERS

Post Hydrants shall be non-freezing, self draining type with a 'bury. These hydrants will be furnished with a 2" FIP horizontal inlet, a non-turning operating rod, and shall open left. Bronze operating mechanism and aluminum plunger. design, and be servicable from above grade with no digging. The outlet shall also be bronze and be 2-1/2" NST. Hydrants shall be lockable to prevent unauthorized use as manufactured by Kupferle Foundry Co., St. Louis, MO, or approved equal.

	Inlet	Pressure (p 75 100 125 150	#Now Rate (gpm) 675 742 800 856	}			DRAWN F.M. APPROV	ED	Star Car
					THIS DRAWING IS THE PROPERTY OF THE KUPFERLE FOUNDRY COMPANY. IT IS NOT TO BE USED OR DUPLICATED WITHOUT PERMISSION OF THE OWNER.		DATE 1-30-	13	KUPFERLE FOUNDRY COMPANY 2511 NORTH 9TH STREET, ST. LOUIS, MO 63102 314-231-6738 800-231-3990 FAX 314-231-2820 http://www.hydrants.com
DA	ATE.	RE.	VISION		PART NO. #77 MAINGUARD POST HYDRANT	SHEET	1 OF	1	пар:/www.nyarana.com

## **#77 MAINGUARD POST HYDRANT**



	75 100 125	Flow Rate (gpm) 380 435 488			Frank Approved	State 1877
	150 822		THIS DRAWING IS THE PROPERTY OF THE KUPFERLE FOUNDRY COMPANY. IT IS NOT TO B			KUPFERLE FOUNDRY COMPANY
DATE	DATE REVISION		USED OR DUPLICATED WITHOUT PERMISSION THE OWNER.  PART NO. 477 MAINGUARD POST HYDRANT	SHEET	MATL 1 OF 1	2511 NORTH 9TH STREET, ST. LOUIS, MO 63102 314-231-8738 800-231-3990 FAX 314-231-2620 http://www.hydrants.com