

SAFETY DATA SHEET

Issue Date 01-Sep-2020 **Revision Date** 26-Jan-2024 **Version** 2.5 **Page** 1 / 14

1. IDENTIFICATION

Product identifier

Product Name Blanking Reagent for Ultra Low Range Chlorine

Other means of identification

Product Code(s) 2493023

Safety data sheet number M01116

UN/ID no UN3265

Recommended use of the chemical and restrictions on use

Recommended Use Water Analysis.

Uses advised against None. Restrictions on use None.

Details of the supplier of the safety data sheet

Manufacturer Address

Hach Company, P.O.Box 389, Loveland, CO 80539, USA, +1(970) 669-3050

Emergency telephone number

+1(303) 623-5716 - 24 Hour Service

2. HAZARDS IDENTIFICATION

Classification

Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Corrosive to metals	Category 1
Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3

Hazards not otherwise classified (HNOC)

Not applicable

Label elements

Signal word

Danger

EN / AGHS Page 1/14

Product Name Blanking Reagent for Ultra Low Range Chlorine **Revision Date** 26-Jan-2024

Page 2/14



Hazard statements

H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

Precautionary statements

P260 - Do not breathe dusts or mists

P280 - Wear protective gloves, protective clothing, eye protection, and face protection

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 - Wash contaminated clothing before reuse

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

P234 - Keep only in original container

P390 - Absorb spillage to prevent material damage

Other Hazards Known

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

Percent ranges are used where confidential product information is applicable.

Chemical name	CAS No	Percent Range	HMRIC #
Propanedioic acid	141-82-2	20 - 30%	-

4. FIRST AID MEASURES

Description of first aid measures

EN / AGHS Page 2/14

Product Name Blanking Reagent for Ultra Low Range Chlorine

Revision Date 26-Jan-2024

Page 3/14

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical

advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open

while rinsing. Do not rub affected area. Get immediate medical advice/attention.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Get immediate medical advice/attention.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Do NOT induce vomiting. Get immediate medical

advice/attention.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood

pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the

chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition

can lead to release of irritating gases and vapors.

Hazardous combustion products This material will not burn.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

U.S. NoticeOnly persons properly qualified to respond to an emergency involving hazardous

substances may respond to a spill according to federal regulations (OSHA 29 CFR

1910.120(a)(v)) and per your company's emergency response plan and

guidelines/procedures. See Section 13, Special Instructions for disposal assistance. Outside of the US, only persons properly qualified according to state or local regulations should

EN / AGHS Page 3/14

Product Name Blanking Reagent for Ultra Low Range Chlorine

Revision Date 26-Jan-2024

Page 4/14

respond to a spill involving chemicals.

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Attention! Corrosive material. Evacuate personnel to

safe areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Should not be released into the

environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust). Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before

reuse. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Flammability class Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies

Appropriate engineering controls

Engineering Controls Showers

Siloweis

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

EN / AGHS Page 4/14

Product Name Blanking Reagent for Ultra Low Range Chlorine

Revision Date 26-Jan-2024

Page 5/14

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hand Protection Wear suitable gloves. Impervious gloves. Barrier creams may help to protect the exposed

areas of skin. Gloves must be inspected prior to use. The selected protective gloves have to satisfy the specifications of EU Directive 2016/425 and the standard EN 374 derived from it. Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN

374-1:2016.

Eye/face protection Face protection shield.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Avoid

contact with eyes, skin and clothing.

General Hygiene Considerations Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this

product. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Wash hands before breaks and immediately after handling the product.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained. Do not allow

into any sewer, on the ground or into any body of water.

Thermal hazards None under normal processing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state

Liquid

Appearance aqueous solution

ous solution Color colorless

Odor Odorless Odor threshold No data available

Property Values Remarks • Method

Molecular weight No data available

pH 0.54 @ 23 °C

Melting point / freezing point \sim -6 °C / 21.2 °F

Initial boiling point and boiling range 99 °C / 210.2 °F

Evaporation rate 0.01 (water = 1)

Vapor pressure 22.577 mm Hg / 3.01 kPa at 25 °C / 77 °F

Relative vapor density 0.62

Specific gravity - VALUE 1 1.09

Partition coefficient Not applicable

Soil Organic Carbon-Water Partition

Coefficient

Not applicable

Autoignition temperature No data available

Decomposition temperatureNo data available

Dynamic viscosity No data available

Kinematic viscosity

No data available

EN / AGHS Page 5/14

Product Name Blanking Reagent for Ultra Low Range Chlorine **Revision Date** 26-Jan-2024

Page 6 / 14

Solubility(ies)

Water solubility

Water solubility classification	Water solubility_	Water Solubility Temperature_
Soluble	> 1000 mg/L	25 °C / 77 °F

Solubility in other solvents

Chemical Name_	Solubility classification	<u>Solubility</u>	Solubility Temperature_
Acid	Soluble	> 1000 mg/L	25 °C / 77 °F

Other information

Metal Corrosivity

Classified as corrosive to metal according to GHS criteria

Steel Corrosion Rate Aluminum Corrosion Rate 21.84 mm/yr / 0.86 in/yr 0.76 mm/yr / 0.03 in/yr

Volatile Organic Compounds (VOC) Content

Chemical name	CAS No	Volatile organic compounds (VOC) content	CAA (Clean Air Act)
Propanedioic acid	141-82-2	No data available	1

Explosive properties

Upper explosion limitNo data availableLower explosion limitNo data available

Flammable properties

Flash point No data available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
No data available
No data available

Oxidizing properties
No data available.

Bulk density
No data available

10. STABILITY AND REACTIVITY

Reactivity

Corrosive on contact with water. Corrosive to metal.

Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Possibility of hazardous reactions

EN / AGHS Page 6/14

Product Name Blanking Reagent for Ultra Low Range Chlorine **Revision Date** 26-Jan-2024

Page 7 / 14

None under normal processing.

Hazardous polymerization

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Oxidizing agent. Acids. Bases.

Hazardous decomposition products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. Causes severe

burns. Avoid contact with skin and clothing.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung

damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing.

Acute toxicity

Based on available data, the classification criteria are not met

Mixture

No data available.

Ingredient Acute Toxicity Data

No data available.

Chemical name	Endpoint type	Reported dose	Exposure time	Toxicological effects	Key literature references and sources for data
Propanedioic acid (20 - 30%) CAS#: 141-82-2	Rat LD ₅₀	1310 mg/kg	None reported	None reported	EPA
Chemical name	Endpoint type	Reported dose	Exposure time	Toxicological effects	Key literature references and sources for data
Propanedioic acid (20 - 30%)	Rat LC ₅₀	> 2225 mg/L	4 hours	None reported	EPA

EN / AGHS Page 7/14

Product Name Blanking Reagent for Ultra Low Range Chlorine **Revision Date** 26-Jan-2024

Page 8 / 14

CAS#: 141-82-2	
----------------	--

Unknown Acute Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity.

Acute Toxicity Estimations (ATE)

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	No information available mg/kg		
ATEmix (dermal)	No information available		
ATEmix (inhalation-dust/mist)	6.30 mg/l		
ATEmix (inhalation-vapor)	46.00 mg/l		
ATEmix (inhalation-gas)	No information available		

Skin corrosion/irritation

Causes severe burns.

Mixture

No data available.

Ingredient Skin Corrosion/Irritation Data

No data available.

Chemical name	Test method	Species	Reported dose	Exposure time	Results	Key literature references and sources for data
Propanedioic acid (20 - 30%) CAS#: 141-82-2	Standard Draize Test	Rabbit	500 mg	24 hours	Mild skin irritant	Vendor SDS

Serious eye damage/irritation

Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.

Mixture

No data available.

Ingredient Eye Damage/Eye Irritation Data

No data available.

Chemical name	Test method	Species	Reported dose	Exposure time	Results	Key literature references and sources for data
Propanedioic acid (20 - 30%) CAS#: 141-82-2	Standard Draize Test	Rabbit	100 mg	None reported	Eye irritant	Vendor SDS

Respiratory or skin sensitization

Based on available data, the classification criteria are not met.

Mixture

No data available.

Ingredient Sensitization Data

No data available.

STOT - single exposure

May cause respiratory irritation.

Mixture

No data available.

Ingredient Specific Target Organ Toxicity Single Exposure Data

EN / AGHS Page 8/14

Product Name Blanking Reagent for Ultra Low Range Chlorine **Revision Date** 26-Jan-2024

Page 9/14

No data available.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Mixture

No data available.

Ingredient Specific Target Organ Toxicity Repeat Exposure Data

No data available.

Carcinogenicity

Based on available data, the classification criteria are not met.

Mixture

No data available.

Ingredient Carcinogenicity Data

No data available.

Chemical name	CAS No	ACGIH	IARC	NTP	OSHA
Propanedioic acid	141-82-2	-	-	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)	Does not apply
IARC (International Agency for Research on Cancer)	Does not apply
NTP (National Toxicology Program)	Does not apply
OSHA	Does not apply

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Mixture invitro Data

No data available.

Substance invitro Data

No data available.

Mixture invivo Data

No data available.

Substance invivo Data

No data available.

Chemical name	Test	Species	Reported dose	Exposure time	Results	Key literature references and sources for data
Propanedioic acid (20 - 30%) CAS#: 141-82-2	Morphological transformation	Rat	10080 mg/kg	6 weeks	Positive test result for mutagenicity	RTECS

Reproductive toxicity

Based on available data, the classification criteria are not met.

Mixture

No data available.

Ingredient Reproductive Toxicity Data

No data available.

Aspiration hazard

EN / AGHS Page 9/14

Product Name Blanking Reagent for Ultra Low Range Chlorine **Revision Date** 26-Jan-2024

Page 10 / 14

Based on available data, the classification criteria are not met.

12. ECOLOGICAL INFORMATION

Ecotoxicity Based on available data, the classification criteria are not met.

Unknown aquatic toxicity 0% of the mixture consists of components(s) of unknown hazards to the aquatic

environment.

Mixture

Aquatic Acute Toxicity

No data available.

Aquatic Chronic Toxicity

No data available.

Substance

Aquatic Acute Toxicity

No data available.

Chemical name	Exposure time	Species	Endpoint type	Reported dose	Key literature references and sources for data
Propanedioic acid (20 - 30%) CAS#: 141-82-2	48 Hours	Daphnia magna	EC50	275 mg/L	EPA

Aquatic Chronic Toxicity

No data available.

Persistence and degradability

Mixture

No data available.

Mixture

No data available.

Partition coefficient Not applicable

Mobility

products

Soil Organic Carbon-Water Partition Coefficient Not applicable

Other adverse effects
No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number D002

EN / AGHS Page 10/14

Product Name Blanking Reagent for Ultra Low Range Chlorine

Revision Date 26-Jan-2024

Page 11/14

Special instructions for disposal

If permitted by regulation. Dilute material with excess water making a weaker than 5% solution. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system. Dispose of material in an E.P.A. approved hazardous waste facility.

14. TRANSPORT INFORMATION

DOT

UN/ID no UN3265

Proper shipping name Corrosive liquid, acidic, organic, n.o.s

DOT Technical Name (Malonic Acid Solution)

Transport hazard class(es) 8
Packing Group III
Emergency Response Guide 153

Number

<u>TDG</u>

UN/ID no UN3265

Proper shipping name Corrosive liquid, acidic, organic, n.o.s

TDG Technical Name (Malonic Acid Solution)

Transport hazard class(es) 8
Packing Group | | | |

IATA

UN number or ID number UN3265

Proper shipping name Corrosive liquid, acidic, organic, n.o.s

IATA Technical Name (Malonic Acid Solution)

Transport hazard class(es) 8
Packing group III
ERG Code 153

IMDG

UN number or ID number UN3265

Proper shipping name Corrosive liquid, acidic, organic, n.o.s

IMDG Technical Name (Malonic Acid Solution)

Transport hazard class(es) 8
Packing Group | | | | |

Additional information

There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is not in a reagent set or kit, the classification given above applies.

If the item is part of a reagent set or kit the classification would change to the following:

UN3316 Chemical Kit, Hazard Class 9, Packing Group II or III.

If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories

TSCA Complies DSL/NDSL Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

International Inventories

EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies

EN / AGHS Page 11/14

Product Name Blanking Reagent for Ultra Low Range Chlorine

Revision Date 26-Jan-2024

Page 12 / 14

TCSI Complies AICS Complies NZIOC Complies

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TCSI - Taiwan Chemical Substances Inventory

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

U.S. EPA Label Information

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Special Comments

None

Additional information

Global Automotive Declarable Substance List (GADSL)

Not applicable

NFPA and HMIS Classifications

EN / AGHS Page 12/14

Product Name Blanking Reagent for Ultra Low Range Chlorine Revision Date 26-Jan-2024
Page 13 / 14

STEL (Short Term Exposure Limit)

NFPA	Health hazards - 3	Flammability - 0	Instability - 0	Physical and chemical properties -
HMIS	Health hazards - 3	Flammability - 0	Physical hazards - 0	Personal protection - X - I

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH (American Conference of Governmental Industrial Hygienists)

ATSDR ATSDR (Agency for Toxic Substances and Disease Registry)
CCRIS (Chemical Carcinogenesis Research Information System)

CDC (Center for Disease Control)

CEPA CEPA (Canadian Environmental Protection Agency)

CICAD CICAD (Concise International Chemical Assessment Documents)

ECHA ECHA (The European Chemicals Agency)
EEA EEA (European Environment Agency)
EPA EPA (Environmental Protection Agency)

ERMA ERMA (New Zealands Environmental Risk Management Authority)

ECOSARS Estimation through ECOSARS v1.11 part of the Estimation Programs Interface (EPI) Suite™

FDA FDA (Food & Drug Administration)

GESTIS GESTIS (Information System on Hazardous Substances of the German Social Accident

Insurance)

HSDB HSDB (Hazardous Substances Data Bank)

INERIS
INERIS (The National Industrial Environment and Risks Institute)
IPCS INCHEM
IPCS INCHEM (International Programme on Chemical Safety)
IUCLID
IUCLID (The International Uniform Chemical Information Database)
NITE
Japan National Institute of Technology and Evaluation (NITE)

NIH (National Institutes of Health)

NIOSH NIOSH (National Institute for Occupational Safety and Health)
LOLI (List of Lists - An International Chemical Regulatory Database)

NDF no data

NICNAS Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH IDLH Immediately Dangerous to Life or Health

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEEN (Pan European Ecological Network)

RTECS (Registry of Toxic Effects of Chemical Substances)
SIDS (Screening Information Dataset) for High Volume Chemicals

SYKE The Finnish Environment Institute (SYKE)
USDA USDA (United States Department of Agriculture)
USDC USDC (United States Department of Commerce)

WHO (World Health Organization)

TWA (time-weighted average)

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

MAC	Maximum Allowable Concentration	Ceiling	Ceiling Limit Value
X	Listed	Vacated	These values have no official status. The only binding levels of contaminants are those listed in the final OSHA PEL. These lists are for reference purposes only. Please note that some reference state regulations of these "liberated" exposure limits in their state regulations.
SKN*	Skin designation	SKN+	Skin sensitization

STEL

SKN* Skin designation SKN+ Skin sensitization
RSP+ Respiratory sensitization ** Hazard Designation
C Carcinogen R Reproductive toxicant

M mutagen

TWA

EN / AGHS Page 13/14

Product Code(s) 2493023 Issue Date 01-Sep-2020

Version 2.5

Product Name Blanking Reagent for Ultra Low Range Chlorine

Revision Date 26-Jan-2024

Page 14 / 14

Prepared By Hach Product Compliance Department

Issue Date 01-Sep-2020

Revision Date 26-Jan-2024

Revision Note None

Disclaimer

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY©2023

End of Safety Data Sheet

EN / AGHS Page 14/14