

SECTION 1: Product and company identification

Product name : Super High Heat
 Use of the substance/mixture : Drain opener
 Product code : 0618
 Company : Total Solutions
 P.O. Box 240014
 Milwaukee, WI 53224 - USA
 T (414) 354-6417
 Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


GHS US classification

Acute Tox. 4 (Dermal) H312
 Skin Corr. 1A H314

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
 Hazard statements (GHS US) : Harmful in contact with skin
 Causes severe skin burns and eye damage
 Precautionary statements (GHS US) : Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: rinse mouth. Do NOT induce vomiting
 If on skin: Wash with plenty of water
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If inhaled: Remove person to fresh air and keep comfortable for breathing
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor
 Call a poison center or doctor if you feel unwell
 Specific treatment (see supplemental first aid instruction on this label)
 Specific treatment (see supplemental first aid instruction on this label)
 Take off contaminated clothing and wash it before reuse.
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS US classification
sodium hydroxide	(CAS-No.) 1310-73-2	75 - 90	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314

Super High Heat

Safety Data Sheet

TOTAL SOLUTIONS™

Name	Product identifier	%	GHS US classification
SODIUM NITRATE	(CAS-No.) 7631-99-4	7 - 13	Ox. Sol. 3, H272 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Get medical advice/attention.
First-aid measures after ingestion	: Fatal if swallowed. Immediately call a poison center or doctor/physician. Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: May cause respiratory irritation. Corrosive to the respiratory tract.
Symptoms/effects after skin contact	: Caustic burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Corrosion of the eye tissue. Permanent eye damage.
Symptoms/effects after ingestion	: Fatal if swallowed. Burns to the gastric/intestinal mucosa.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Reactivity : Reacts violently with water. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water moderately and if possible collect or contain it. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Protective goggles. Face-shield.
Emergency procedures	: Keep upwind.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent soil and water pollution.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released product, pump into suitable containers.
Methods for cleaning up	: Absorb spillage to prevent material-damage. Solid spill: shovel. This material and its container must be disposed of in a safe way, and as per local legislation. Spill must not return in its original container.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store in original container.

Incompatible products : Strong acids.

Storage area : Keep only in the original container. Store in a dry area. Store in a cool area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sodium hydroxide (1310-73-2)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
ACGIH	Remark (ACGIH)	URT, eye, & skin irr
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
sodium carbonate (497-19-8)		
Not applicable		
SODIUM NITRATE (7631-99-4)		
Not applicable		

8.2. Exposure controls

Personal protective equipment : Face shield. Gloves. Safety glasses. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Red granules.

Odor : No odor

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : No data available

Explosion limits : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Vapor pressure : No data available

Relative density : No data available

Relative vapor density at 20 °C : No data available

Solubility : Soluble in water.

Log Pow : No data available

Log Kow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Super High Heat

Safety Data Sheet

Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with water. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

Reacts violently with water.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

May be corrosive to metals. Strong acids. metals.

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium hydroxide (1310-73-2)	
LD50 oral rat	4090 mg/kg
LD50 dermal rabbit	1350 mg/kg
ATE CLP (oral)	4090 mg/kg body weight
ATE CLP (dermal)	1350 mg/kg body weight
sodium carbonate (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg (16 CFR 1500. 40, 24 h, Rabbit, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	(2 h, Rat, Male, Experimental value)
ATE CLP (oral)	2800 mg/kg body weight
ATE CLP (vapors)	2.3 mg/l/4h
ATE CLP (dust, mist)	2.3 mg/l/4h
SODIUM NITRATE (7631-99-4)	
LD50 oral rat	1267 mg/kg
ATE CLP (oral)	1267 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Eye damage, category 1, implicit
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified
Specific target organ toxicity – repeated exposure : Not classified
Aspiration hazard : Not classified
Symptoms/effects after inhalation : May cause respiratory irritation. Corrosive to the respiratory tract.
Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.
Symptoms/effects after eye contact : Causes serious eye irritation. Corrosion of the eye tissue. Permanent eye damage.
Symptoms/effects after ingestion : Fatal if swallowed. Burns to the gastric/intestinal mucosa.

SECTION 12: Ecological information

12.1. Toxicity

Super High Heat

Safety Data Sheet

sodium carbonate (497-19-8)	
LC50 fish 1	300 mg/l (96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	200 - 227 mg/l (48 h, Ceriodaphnia sp., Semi-static system, Fresh water, Experimental value, Locomotor effect)

SODIUM NITRATE (7631-99-4)	
LC50 fish 1	6650 mg/l static test LC50 - Gambusia affinis (Mosquito fish)

12.2. Persistence and degradability

sodium carbonate (497-19-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

sodium carbonate (497-19-8)	
Log Pow	-6.19 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN3262 Corrosive solid, basic, inorganic, n.o.s. (Sodium Hydroxide), 8, II
 UN-No.(DOT) : UN3262
 Proper Shipping Name (DOT) : Corrosive solid, basic, inorganic, n.o.s.
 Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
 Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : II - Medium Danger
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 212
 DOT Packaging Bulk (49 CFR 173.xxx) : 240
 DOT Symbols : G - Identifies PSN requiring a technical name
 DOT Special Provisions (49 CFR 172.102) : IB8,IP2,IP4,T3,TP33
 DOT Packaging Exceptions (49 CFR 173.xxx) : 154
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 15 kg
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 50 kg
 DOT Vessel Stowage Location : B
 DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Emergency Response Guide (ERG) Number : 154
 Other information : When transported by ground, this product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.154. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

ADR

No additional information available

Super High Heat

Safety Data Sheet

Transport by sea

UN-No. (IMDG) : 3262
Proper Shipping Name (IMDG) : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.
Class (IMDG) : 8 - Corrosive substances
Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 3262
Proper Shipping Name (IATA) : Corrosive solid, basic, inorganic, n.o.s.
Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

sodium hydroxide (1310-73-2)	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	1000 lb

WARNING

This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H272	May intensify fire; oxidizer
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity : 2 - Materials that readily undergo violent chemical change at elevated temperatures and pressures.
NFPA specific hazard : W - Materials that react violently or explosively with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.