



**WACKER  
NEUSON**  
*all it takes!*

## BOC7 US

5100069475

[Home](#) >> [Catalog](#) >> [Products](#) >> [Power supply](#) >> [Power Storage](#) >> [Batteries & Charger](#) >> **BOC7 US**

## BOC7 US

Material number 5100069475

Standard charger.



### Product details

#### Highlights

- Battery One battery system
- Systainer transport box

### Comes with

- Charger

Technical specifications

BOC7 US

ELECTRICAL - OUTPUT DETAILS	Imperial	Metric
Nominal current	1,30 - 3,50 A	1,30 - 3,50 A
Nominal Output Voltage	36,0 V	36,0 V
Phase	1 ~	1 ~
Nominal voltage	120 - 240 V	120 - 240 V
Kind of current (Output)	DC	DC
Nominal frequency	50 - 60 Hz	50 - 60 Hz
Nominal power [P]	0,35 kW	0,35 kW
Output Voltage Range	1,8 - 60,0 V	1,8 - 60,0 V
End-of-charge voltage	58,4 V	58,4 V
Output current	7,5 A	7,5 A

ELECTRICAL SYSTEM	Imperial	Metric
Kind of plug	NEMA 5-15P (Type B)	NEMA 5-15P (Type B)
Length Cable	6,6 Foot	2,00 m
Breaker Switch On/Off	no	no

ENVIRONMENT DATA	Imperial	Metric
Operating temperature range	32 - 113 °F	0 - 45 °C
Protection class	I / Protective earthing	I / Protective earthing
Storage temperature range	-4 - 140 °F	-20 - 60 °C
Degree of protection	IP66	IP66

MECHANICAL DETAILS	Imperial	Metric
Length	7,9 "	200 mm
Height	2,4 "	60 mm
Width	5,7 "	145 mm

Weight	4,41 lb	2,00 kg
--------	---------	---------

---

**Please Note**

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE