



**WACKER
NEUSON**
all it takes!

BOC13 US

5100069477

[Home](#) >> [Catalog](#) >> [Products](#) >> [Power supply](#) >> [Power Storage](#) >> [Batteries & Charger](#) >> **BOC13 US**

BOC13 US

Material number 5100069477

Fast-charger integrated in the Systainer transport box.



Product details

Highlights

- Battery One battery system
- Systainer transport box

Comes with

- Charger

Technical specifications

BOC13 US

ELECTRICAL - OUTPUT DETAILS	Imperial	Metric
Nominal current	2,90 - 7,30 A	2,90 - 7,30 A
Nominal Output Voltage	48,0 V	48,0 V
Phase	1 ~	1 ~
Nominal voltage	100 - 240 V	100 - 240 V
Kind of current (Output)	DC	DC
Nominal frequency	50 - 60 Hz	50 - 60 Hz
Nominal power [P]	0,65 kW	0,65 kW
Output Voltage Range	2,7 - 60,0 V	2,7 - 60,0 V
End-of-charge voltage	58,2 V	58,2 V
Output current	13,5 A	13,5 A

ELECTRICAL SYSTEM	Imperial	Metric
Cooling system	aktive Kühlung	aktive Kühlung
Kind of plug	NEMA 5-15P (Type B)	NEMA 5-15P (Type B)
Length Cable	6,6 Foot	2,00 m
Breaker Switch On/Off	no	no

ENVIRONMENT DATA	Imperial	Metric
Operating temperature range	32 - 113 °F	0 - 45 °C
Protection class	I / Protective earthing	I / Protective earthing
Storage temperature range	-4 - 140 °F	-20 - 60 °C
Degree of protection	IP65	IP65

MECHANICAL DETAILS	Imperial	Metric
Length	11,7 "	296 mm
Height	8,5 "	217 mm

Width	15,6 "	396 mm
Weight	11,68 lb	5,30 kg

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE