



**WACKER
NEUSON**
all it takes!

Introducing **Generators** Portable



Dependable portable power

Wacker Neuson's portable generators are perfect to keep job sites running smoothly. Designed for construction and rental, these quiet, high-performance generators deliver reliable power in a rugged, compact package.



Versatility for the job site

These portable generators offer excellent tool starting and voltage regulation making them ideal for powering single or multiple tools on an entire job site or an emergency standby power.

Performance

- Powered by Honda engines and paired with Mecc Alte alternators to provide reliable, clean and consistent power
- Selectable voltage setting allows for maximum power usage

Efficiency

- Auto idle control reduces the engine to lower speed when no load is detected, saving on fuel and extending machine life
- Solid wheels and flip-up handle provide for easy and convenient transport on the job site and in the shop

Maintenance

- High impact polyethylene fuel tank and heavy-duty shock mounting combined to provide outstanding impact protection



Performance Data

	Unit	GP2500A	GP4000A includes wheel kit	GP5500A includes wheel kit	GP7000A Includes wheel kit
Length x width x height with wheel kit	in	18 x 24 x 19	21 x 27.5 x 24	21 x 27.5 x 24	21 x 27.5 x 24
Operating weight	lbs	99	166	174	174
Maximum output	W	2,500	4,000	5,500	7,200
Continuous output	W	2,250	3,800	5,000	6,800
Continuous AC amps	A	19 / 9	32 / 16	42 / 21	57 / 28
AC voltage	V	120 / 240	120 / 240	120 / 240	120 / 240
AC circuit breaker amps	A	20 / 1 pole	18 / 1 pole	22 / 1 pole	30 / 1 pole
Frequency	Hz	60	60	60	60
Phase	Ø	1	1	1	1
Power factor	Pf	1	1	1	1
Engine type		Honda, air-cooled, 4-cycle, single-cylinder, gasoline engine.		Honda, air-cooled, 4-cycle, single-cylinder, gasoline engine.	
Starting system		recoil	recoil	recoil	recoil
Displacement	in ³	9.9	16.5	23.7	23.7
Operating speed	rpm	3,600	3,600	3,600	3,600
Max. rated power at rated speed	hp rpm	4.8 @ 3,600	6.8 @ 3,600	9.4 @ 3,600	9.4 @ 3,600
Fuel tank capacity	gal	3.9	7.9	7.9	7.9
Running time / full load	hrs	10	12.5	8.5	8.5
AC outlet receptacles Duplex Twist Lock		(2) 125V, 20A GFCI Duplex 5-20R	(2) 125V, 20A GFCI Duplex 5-20R (1) 125/250V, 30A Twist Lock L14-30R (1) 125V, 30A Twist Lock L5-30R	(2) 125V, 20A GFCI Duplex 5-20R (1) 125/250V, 30A Twist Lock L14-30R (1) 125V, 30A Twist Lock L5-30R	
CSA certified		yes	yes	yes	yes